

# SF-IPD820WA-4E

4 MP IP Camera

1/3" Progressive Scan CMOS

2.8 mm Lens

Compression H.265+|H.264+

Protection IK10 Antivandalism

protection

IR LEDs Range 30 m

PoE IEEE802.3af | IP67



Safire

IP camera

1/3" Progressive Scan CMOS

4 Megapixel (2560x1440)

2.8 mm Lens

0 Lux

IR Range 30 m

H.265+/H.265/H.264+/H.264

Dual stream

IR Cut

Internal Storage MicroSD Card

RJ45 10/100 BaseT

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

PoE IEEE802.3af

Weatherproof IP67

Vandal proof IK10

# Specifications

Brand	SAFIRE
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	20 fps (2560 x 1440) 25 fps (2304 x 1296, 1920 x 1080, 1280x720)
Extra Stream rate	25 fps (640 x 480, 640 x 360, 320 x 240)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	32 Kbps – 8 Mbps
Lens	2.8 mm
Pan/Tilt Range	Horizontal: 0°~355°, Vertical: 5°~75°
Minimum illumination	0.01 Lux F1.2
Infrared lighting	0 Lux / IR LEDs (30 m)
Image improvements	WDR, BLC, 3D-DNR, Mirror, Privacy Mask, Watermark, Anti-Flicker
Event	Motion Detection, Exception
Day / Night	Removable mechanical ICR filter
Internal memory	Micro SD card (up to 256 GB)
Network interface	Ethernet 10/100M BaseT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	DC 12 V / 400 mA / 5 W, PoE IEEE802.3af
Degree of protection	Waterproof IP67   IK10 Anti-vandalism
Temp. operation	-30° C ~ +60° C
Dimensions	92.2 (H) x 120 (Ø) mm
Base dimensions	104.7 (Ø) mm / 3 screws
Weight	440 g