

# SF-NVR6104-4KE-4P

NVR for IP cameras

4 CH video PoE+ 50W / Compression

H.265+

Maximum resolution 8.0 Mpx

Bandwidth 40 Mbps

Outputs 4K HDMI & VGA

Supports 1 hard disk



Safire

NVR for IP cameras

4 CH

40 Mbps bandwidth supported

Maximum resolution 8 Megapixel (4096x2160)

Compression H.265+/H.265/H.264+/H.264

VGA and HDMI 4K output

IP Dual Stream Access

Mouse

Space for 1 HDD

4 PoE ports IEEE802.3af/at

WEB, CMS and Smartphone interface

ONVIF Compatible

# Specifications

<b>Brand</b>	Safire
<b>Inputs for IP cameras</b>	LAN port up to 4 PoE channels
<b>Power over Ethernet</b>	4 (Max. 50W)
<b>IP compatible cameras</b>	SAFIRE (native protocol), ONVIF
<b>Bidirectional audio</b>	1 input / 1 RCA output
<b>Video outputs</b>	1 HDMI 4K, 1 VGA
<b>Video compression format</b>	H.265+ / H.265 / H.264+ / H.264
<b>Display resolution</b>	3840x2160, 2560x1440, 1920x1080, 1280x1024, 1280x720, 1024x768
<b>Total bandwidth</b>	40 Mbps downstream / 80 Mbps upstream
<b>Main Stream recording</b>	8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
<b>Simultaneous multifunction</b>	Pentaplex: Live, Recording, Playback, Backup and Remote Access
<b>Alarms</b>	No
<b>Recording method</b>	Manual, programmed, motion detection
<b>External Backup</b>	USB memory / HDD USB / CD-RW USB / DVR-RW USB
<b>Internal memory</b>	1 SATA HDD 3.5" of up to 6 TB (not included)
<b>Communication</b>	1 x USB 2.0 (front) / 1 x USB 2.0 / 1 x RJ45 (Ethernet)
<b>Remote access</b>	Web browser, Safire Control Center Smartphone App and PC Software
<b>Power</b>	DC 48V / 1.35A
<b>Dimensions / Weight</b>	48 (H) x 320 (W) x 240 (D) mm / 0.9 Kg