

SF-NVR6108-4KE-8P

NVR for IP cameras

8 CH video / Compression H.265+

8 PoE Channels

Maximum resolution 8Mpx

Bandwidth 80 Mbps

Outputs 4K HDMI & VGA

Supports 1 hard disk



Safire

NVR for IP cameras

8 CH

80 Mbps bandwidth supported

Maximum resolution 8 Megapixel (4096x2160)

Compression H.265+/H.265/H.264+/H.264

VGA and HDMI 4K output

IP Dual Stream Access

Mouse

Space for 1 HDD

8 PoE ports IEEE802.3af/at

WEB, CMS and Smartphone interface

ONVIF Compatible

Specifications

Brand	Safire
Inputs for IP cameras	LAN port up to 8 channels
Power over Ethernet	8 port PoE Switch IEEE802.3af/at (max. 75 W)
IP compatible cameras	SAFIRE (native protocol), ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	H.265+ / H.265 / H.264+ / H.264
Display resolution	4K (4096 x 2160), 4K (3840 2160), x 2K (2560 1440), x [%VAR%] 1920 x 1080, 1600 x 1200, 1280 x 1024, 1280 720 x [%VAR%]
Total bandwidth	80 Mbps downstream / 80 Mbps upstream
Main Stream recording	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	No
Audio	1 Input / 1 Output
Recording method	Manual, programmed, motion detection
External Backup	USB / HDD USB memory
Internal memory	1 SATA HDD 3.5" of up to 8 TB (not included)
Communication	2 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Power	DC 48V / 1.88 A / 10 W max.
Dimensions / Weight	48 (H) x 320 (W) x 240 (D) mm / 1 Kg