

SF-NVR8208A-4K8P

NVR for IP cameras

8 CH video / Compression H.265+

8 PoE Channels

Maximum resolution 12.0 Mpx

Bandwidth 80 Mbps

Outputs 4K HDMI & VGA



Safire

NVR for IP cameras

8 CH

80 Mbps bandwidth supported

Maximum resolution 12 Megapixel

Compression H.265+/H.265/H.264+/H.264

ANR (Automatic Network Replenishment)

Alarms

VGA and HDMI 4K output

IP Dual Stream Access

Mouse

Space for 2 HDD

8 PoE ports

WEB, CMS and Smartphone interface

ONVIF Compatible

Specifications

Brand	Safire
Inputs for IP cameras	LAN port up to 8 channels
Power over Ethernet	Up to 8 channels
IP compatible cameras	SAFIRE (native protocol), ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	H.265+/H.265 / H.264+ / H.264
Display resolution	3840x2160, 2560x1440, 1920x1080, 1280x1024, 1280x720, 1024x768
Total bandwidth	80 Mbps downstream / 256 Mbps upstream
Main Stream recording	12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	4 Inputs / 1 Relay NO/NC
Recording method	Manual, programmed, motion detection, alarm
External Backup	USB memory / HDD USB / CD-RW USB / DVR-RW USB
Internal memory	2 SATA HDD 3.5" of up to 6 TB (not included)
Communication	1 x USB 3.0 / 1 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Power	VAC 100 ~ 240 Frequency 50 Hz / 180 W
Dimensions / Weight	45 (H) x 380 (W) x 290 (D) mm / 3 Kg